

### **PIES Australia Pty Ltd**

49 Freight Drive, Somerton Victoria 3062 P.O. Box 425, Somerton Victoria 3062

Phone: (03) 9303 2000 Fax: (03) 9303 2099 E-mail: sales@piesau.com.au Web: www.piesau.com.au

# SM<sub>5</sub>

## NEW GENERATION TENSION METER FOR ANY BELTS TYPES.

### **PROPERTIES:**

- Back light display (LCD)
- Light beam indicating the right position for the measure.
- Optimized measurement distance, from 2 to 5 cm between the sensor and belts back
- Battery life indicator.
- Very good ergonomics, very easy to use.
- Very good price/ performance ratio .

### **ADVANTAGES:**

Correct pre-tension enhances the operation of any belt drive by :

- Increasing the servicelife and minimizing the bearing load
- Improving both tooth meshing and positioning,
- Reducing noise level.

# Battery life indicator Tension Metar SM5 Back light display LCD Belt-tension measuring Device Reading of the frequency in Hertz I. But largen in maliers before the points (center distance) in Mars of the belt per maker length in lagin Fr. Pre-fermion in Readon Ergonomic security handle

### **SPECIFICITIES OF THE SM5:**

- Frequency range: 7 à 450 Hz.
- Accuracy +/- 5%; ( higher on demand ).
- Supplied with a 9V long-life battery(6LR61)
- · Conform to CE norms
- Automatic delay.